

# DURAVAC

**DURAVAC PRODUCTS LIMITED**  
UNIT 170 JOHN WILSON BUSINESS PARK  
WHITSTABLE, KENT, CT5 3RA  
TEL:01227 770828 - FAX:01227 770878  
Email: [sales@duravac.co.uk](mailto:sales@duravac.co.uk)

## DURAVAC TW68 / TW68A MECHANICAL PUMP OIL

A fully saturated paraffinic oil obtained by hydrotreating, the absence of unsaturated components results in a thermally and chemically stable product. Suitable for the majority of all major manufacturers pumps. Available with antioxidant (TW68A slight tint) or without (TW68 water white). The antioxidant increases lifetime of the oil.

### TYPICAL CHARACTERISTICS

<b>Saturated Vapour Pressure @ 20°C</b>	5.0 X 10 <sup>-7</sup> torr
<b>Average Boiling Range @ 5.0 X 10<sup>-1</sup> torr</b>	-
<b>Mid Range Boiling @ 5.0 X 10<sup>-1</sup> torr</b>	-
<b>Initial Boiling Point @ 5.0 X 10<sup>-1</sup> torr</b>	175°C
<b>Molecular Weight (typical)</b>	-
<b>Flash Point C.o.C</b>	>230°C
<b>Viscosity @ 40°C Nominal</b>	65 cst
<b>Pour point</b>	-30°C
<b>Specific Gravity @ 20°C (Typical):</b>	0.86
<b>Colour</b>	White / Slight tint
<b>Oil Type</b>	Mineral